

MATERIAL SAFETY DATA SHEET

Sales Order: {SalesOrd}

T0001 FAST EVAP REDUCER FOR SPRAY URETHANESMSDS Revision No: A2 -3
MSDS Revision Date: 12/22/2009Akzo Nobel Coatings
Interlux Yacht Finishes
2270 Morris Avenue
P. O. Box 386
Union, NJ 07083**EMERGENCY NUMBERS:**(800) 424-9300 CHEMTREC (USA)
(703) 527-3887 CHEMTREC (Intl)
(800) 854-6813 Poison Control Center
CUSTOMER SERVICE: (Non-Emergency)
(800) 589-1267 International Paint
(800) 631-7481 Interlux**1. GENERAL INFORMATION****Product Identity:** T0001 FAST EVAP REDUCER FOR SPRAY URETHANES**Bulk Sales Reference No:** OT0001

IMPORTANT: Read this MSDS before handling or disposing of this product, and provide this information to the employee, customers, and users of this product. PLEASE NOTE THE MSDS REVISION NUMBER AT THE TOP OF THIS PAGE. If the MSDS Revision Number posted at the top of this page does not match the MSDS Revision Number on the product label, please contact Customer Service at the phone number included above for the correct MSDS. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard.

NOTICE: OSHA hazardous chemicals are listed in Section 2 if present at 1% or more. Carcinogens and extraordinarily/special hazardous chemicals are listed in Section 2 if present at .1% or more. Additional regulatory information for specific chemical categories is included in Section 15.

2. HAZARDOUS INGREDIENT INFORMATION

CAS No.	Ingredient Name & %	Source	Exposure Data
000078-93-3	Butanone 25 - 50% by Weight	OSHA:	200 ppm TWA; 590 mg/m3 TWA300 ppm STEL; 885 mg/m3 STEL
		ACGIH:	200 ppm TWA300 ppm STEL
		NIOSH:	200 ppm TWA; 590 mg/m3 TWA300 ppm STEL; 885 mg/m3 STEL3000 ppm IDLH
		Supplier:	No Established Limit
		OHSA, CAN:	200 ppm TWAEV; 590 mg/m3 TWAEV300 ppm STEV; 885 mg/m3 STEV
		Mexico:	200 ppm TWA; 590 mg/m3 TWA300 ppm STEL; 885 mg/m3 STEL
		Brazil:	155 ppm TWA; 460 mg/m3 TWA
		Source	Health Data
		NIOSH:	Irritation; liver kidney
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No

CAS No.	Ingredient Name & %	Source	Exposure Data
000123-86-4	BUTYL ACETATE 10 - 25% by Weight	OSHA:	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		ACGIH:	150 ppm TWA200 ppm STEL
		NIOSH:	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)
		Supplier:	No Established Limit
		OHSA, CAN:	150 ppm TWAEV; 710 mg/m3 TWAEV200 ppm STEV; 950 mg/m3 STEV
		Mexico:	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		Brazil:	No Established Limit
		Source	Health Data
		NIOSH:	Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals
		Source	Carcinogen Data

OT0001_A2

		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No
CAS No.	Ingredient Name & %	Source	Exposure Data
000141-78-6	Ethylacetate 10 – 25% by Weight	OSHA:	400 ppm TWA; 1400 mg/m3 TWA
		ACGIH:	400 ppm TWA
		NIOSH:	400 ppm TWA; 1400 mg/m3 TWA2000 ppm IDLH (10% LEL)
		Supplier:	No Established Limit
		OHSA, CAN:	400 ppm TWAEV; 1440 mg/m3 TWAEV
		Mexico:	400 ppm TWA; 1400 mg/m3 TWA
		Brazil:	310 ppm TWA; 1090 mg/m3 TWA
		Source	Health Data
		NIOSH:	Eye and respiratory irritation
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No

3. HAZARD IDENTIFICATION

Overview:	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.		
Inhalation:	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.		
Eyes:	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.		
Skin:	Causes skin irritation. Repeated contact can cause dermatitis. May be harmful if absorbed through the skin.		
Ingestion:	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.		
Chronic Effects:			
HMIS Rating:	Health: 2	Flammability: 3	Reactivity: 0

4. FIRST AID MEASURES

General:	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin:	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion:	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

5. PROTECTIVE EQUIPMENT AND CONTROL MEASURES

Respiratory:	Select equipment to provide protection from the ingredients listed in Section 2 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the
--------------	---

OT0001_A2

	accuracy of the information contained in this Material Safety Data Sheet.
Eyes:	Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin/Hand:	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls:	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices:	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

6. FIRE AND EXPLOSION INFORMATION

Flash Point:	F: 20 C: -7
Lower Explosive Limit (LEL):	0 (%vol in air) at Normal Atmospheric Temp and Pressure
Fire and Explosion Hazards:	Extremely flammable liquid and vapor. Vapors may cause flash fire. FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO2, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.
Fire Fighting Procedures:	Also Reference Emergency Response Guide Number: 127

7. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid Coloured
pH:	No Established Limit
Specific Gravity:	0.8811
Boiling Point (F):	0 ERROR!!!
Vapor Density:	Heavier than air
VOC Content (lbs):	Refer to the Technical Data Sheet for this product.
Evaporation Rate:	Slower than ether

8. STABILITY AND REACTIVITY DATA

General:	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials:	Strong oxidizing agents.
Hazardous Decomposition:	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

9. HANDLING AND STORAGE

Storage Temperature:	Store between 40–100F (4–38C).
Handling and Storage Precautions:	Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve

OT0001_A2

cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling.

10. TOXICOLOGICAL DATA

General: NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Section 2 for chemical specific data.

11. ECOLOGICAL DATA

General: No additional information provided for this product. See Section 2 for chemical specific data.

12. ACCIDENTAL RELEASE MEASURES

Spill Response Procedures: ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. **LARGE SPILLS:** Consider initial downwind evacuation for at least 300 meters (1000 feet). Also, Reference Emergency Response Guide Number: 127

Public Safety:

13. DISPOSAL CONSIDERATION

Waste Disposal: Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. TRANSPORTATION INFORMATION

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name: PAINT RELATED MATERIAL		IMDG Proper Shipping Name: PAINT RELATED MATERIAL	
DOT Hazard Class:	3	IMDG Hazard Class:	3.2 – Intermediate flashpoint flammable liquids
UN / NA Number:	UN 1263	UN Number:	UN 1263
DOT Packing Group:	II	IMDG Packing Group:	II
CERCLA/DOT RQ:	1992 gal. / 14620 lbs.	System Reference Code:	32

15. REGULATORY INFORMATION

Regulatory Overview: The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.
Note: Any chemical ingredients listed in Section 15, that do not also appear in Section 2, are contained in the product at a concentration below the applicable OSHA threshold level of 1% or 0.1%.

WHMIS Classification: No Established Limit

Regulatory List Product Ingredients on List

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants

(1%):

(No Product Ingredients

Listed)

EPCRA 311/312 Chemicals and

RQs (>.1%) :

000141-78-6

Ethylacetate : 5000 lb final RQ; 2270 kg final RQ

000078-93-3

Butanone : 5000 lb final RQ; 2270 kg final RQ

000123-86-4

BUTYL ACETATE : 5000 lb final RQ; 2270 kg final RQ

EPCRA 302 Extremely

Hazardous (>.1%) :

(No Product Ingredients

Listed)

EPCRA 313 Toxic Chemicals

(>.1%) :

(No Product Ingredients

Listed)

Mass RTK Substances (>1%) :

000141-78-6

Ethylacetate

000078-93-3

Butanone

000123-86-4

BUTYL ACETATE

Mass Extraordinarily Haz Sub

(>.01%) :

(No Product Ingredients

Listed)

Penn RTK Substances (>1%) :

000141-78-6

Ethylacetate

000078-93-3

Butanone

000123-86-4

BUTYL ACETATE

Penn Special Hazardous

Substances (>.01%) :

(No Product Ingredients

Listed)

Rhode Island Hazardous

Substances (>.1%) :

000141-78-6

Ethylacetate

000078-93-3

Butanone

000123-86-4

BUTYL ACETATE

RCRA Status (%):

000078-93-3

Butanone : 34.2

N.J. RTK Substances (>1%) :

000141-78-6

Ethylacetate

000078-93-3

Butanone

000123-86-4

BUTYL ACETATE

N.J. Special Hazardous

Substances (>.01%) :

000141-78-6

Ethylacetate

000123-86-4

BUTYL ACETATE

N.J. Env. Hazardous Substances

(>.1%) :

(No Product Ingredients

Listed)

Proposition 65 – Carcinogens

(>0%):

(No Product Ingredients

Listed)

Proposition 65 – Female Repro

Toxins (>0%):

(No Product Ingredients

Listed)

Proposition 65 – Male Repro

Toxins (>0%):

(No Product Ingredients

Listed)

Proposition 65 – Developmental

Toxins (>0%):

(No Product Ingredients

Listed)

16. OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

International Paint, LLC, 6001 Antoine Drive, Houston, Texas 77091. <http://www.international-pc.com> or <http://www.international-marine.com>

End Of Document